

chybí obrázek

Odporúčaná cena

0,00 EUR

Technické špecifikácie

vyrábané veľkosti S: 390mm / M: 420mm / L: 470mm / XL: 510mm	rám F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 100mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.
vidlica Fox 34 Step Cast Float FIT4 Evol Factory Kashima, 110mm, tapered steerer tube,15x110mm Boost axle, offset 44mm. Settings: remote 2pos Push-unlock, compression micro-adjustment at low-speed, rebound, air preload	hlavové zloženie Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom
prehadzovačka Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	radenie Sram Trigger GX Eagle, 12s, X-Actuation 1:1
brzdové páčky Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings	kluky Sram X1 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S size: 170mm, M/L/XL size: 175mm
stredové zloženie Sram DUB BSA, sealed bearings, 73mm	riadidlá Onoff Helium Carbon 0.2, rise: 4.8mm, width: 760mm, 9º backsweep, 0º upsweep, 31.8mm barbare
predstavec MDK, 6061 T6 Alloy, 31.8mm barbare, rise: +/-5º, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm	sedlovka Onoff Helium Carbon 0-R, diameter 31.6mm, length 400mm
sedlo Fizik Antares R7	náboj predný Mavic, Boost 15x110mm, IS 6 bolts
náboj zadný Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub	reťaz Sram GX Eagle, 12s, Powerlock
kazeta Sram XG-1275, 10-50T, 12s	drôty Mavic straightpull duble butted, contactless lacing
ráfiky Mavic Crossmax Carbon XL R 29, 30mm internal width, hookless, tubeless ready, 24 spokes	plášte Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead, Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead
obj.c. 010.22048	gripy Onoff Diamond, 1lock-on, 135mm
tlmič Fox Float DPS SV EVOL Factory Kashima, 185x47,5mm. Settings: 2 position remote compression (open/lock), low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings	predná brzda Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad

zadná brzda

Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

nastavenia tlmiče

Firm compression, light rebound, air volume spacer 0.2

prevodník

34T, CNC-machined alloy, X-SYNC 2

pätka k přehazovačce

Sram UDH