

chybí obrázek

Technické špecifikácie

vyrábané veľkosti One size: 350mm	rám Play 26 6061 Alloy Stealth evo, hydroformed tubing, integrated internal non-removable battery, Tapered head tube, HHG internal cable routing, BSA bottom bracket, QR 9mm rear axle, 1x drivetrain compatible
vidlica RockShox Judy Silver TK 26, 100mm, TurnKey, Solo Air, tapered steerer tube, 9x100mm axle, 30mm steel stanchions, 40mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload	hlavové zloženie Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
prehadzovačka Sram NX, 11s, long cage, X-actuation 1:1	radenie Sram trigger NX 11s, X-actuation 1:1
brzdové páčky Sram Level, tooled reach adjust, lever pivot bushings	kľuky Samox DM 30T steel, 152mm
stredové zloženie BSA, 73mm	riadidlá MDK XC 1.0, 6061 alloy, rise: 25mm, width: 650mm, 9° backsweep, 5° upsweep, 31.8mm barbore
predstavec Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore	sedlovka MDK XC 0-R, 6061 T6 Alloy, diameter 31.6mm, length 350mm
sedlo SDG Fly JR	náboj predný Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts
náboj zadný Mahle-Ebikemotion X-35	reťaz Sram PC1110 11s, Powerlock
kazeta Sram PG 1030 11-42T, 11s	drôty CN round stainless steel
ráfiky MDK-XP1 26 TLR, 25mm internal width, tubeless ready, 32 spokes	plášte Kenda Booster 26x2.4 single compound 30TPI, wire bead
obj.c. 010.23209	gripy Onoff Twin, 1lock-on
predná brzda Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	zadná brzda Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
prevodník 30T, steel	pätka k prehadzovačce Mondraker M073
motor + batérie Mahle-Ebikemotion X-35, Mahle-Ebikemotion Internal 250Wh, Mahle-Ebikemotion	