

chybí obrázek

Technické špecifikácie

vyrábané veľkosti One size: 320mm	rám Play 24 6061 Alloy Stealth evo, hydroformed tubing, integrated internal non-removable battery, Tapered head tube, HHG internal cable routing, BSA bottom bracket, QR 9mm rear axle, 1x drivetrain compatible
vidlica RockShox Judy Silver TK 26, 100mm, TurnKey, Solo Air, tapered steerer tube, 9x100mm axle, 30mm steel stanchions, 40mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload	prehadzovačka Sram NX, 11s, long cage, X-actuation 1:1
radenie Sram trigger NX 11s, X-actuation 1:1	brzdové páčky Sram Level, tooled reach adjust, lever pivot bushings
kľuky Samox DM 28T steel, 127mm	stredové zloženie BSA, 73mm
riadidlá MDK XC 1.0, 6061 alloy, rise: 25mm, width: 580mm, 9° backsweep, 5° upsweep, 31.8mm barbare	predstavec Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
sedlovka MDK XC 0-R, 6061 T6 Alloy, diameter 31.6mm, length 300mm	sedlo SDG Fly JR
náboj predný Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts	náboj zadný Mahle-Ebikemotion X-35
reťaz Sram PC1110 11s, Powerlock	kazeta Sram PG 1030 11-42T, 11s
drôty CN round stainless steel	ráfiky MDK-XP1 24 TLR, 25mm internal width, tubeless ready, 32 spokes
plášte Kenda Booster 24x2.4 single compound 30TPI, wire bead	obj.c. 010.23208
gripy Onoff Twin, 1lock-on	predná brzda Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
zadná brzda Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	prevodník 28T, steel
pätka k prehazovačke Mondraker M073	motor + batérie Mahle-Ebikemotion X-35,Mahle-Ebikemotion Internal 250Wh, Mahle-Ebikemotion