

chybí
obrázek

Odporúčaná cena
0,00 EUR

Technické špecifikácie

vyrábané veľkosti S: 380mm / M: 420mm / L: 470mm / XL: 510mm	rám Foxy 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 150mm travel, Forward Geometry, one piece Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, MAX capacity sealed bearings, ISCG 05
vidlica Fox 36 29 Float FIT GRIP EVOL Performance, 160mm, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload	hlavové zloženie Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
prehadzovačka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	radenie Sram Trigger NX Eagle, 12s, X-Actuation 1:1
brzdové páčky Sram G2 RS, SwingLink, tool-free reach adjust	kľuky Sram GX Eagle, Boost, DUB axle, Direct Mount
stredové zloženie Sram DUB BSA, sealed bearings, 73mm	riadidlá Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 780mm, 9° backsweep, 5° upsweep, 31.8mm barbore
predstavec Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore	sedlovka Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M size 387x125mm, L size: 425x150mm, XL size: 465x170mm
sedlo SDG BEL-AIR 3.0, LPU foam, steel rails	náboj predný DT 370, Boost 15x110mm, IS 6 bolts
náboj zadný DT 370, Boost 12x148mm, 3 Pawl system, IS 6 bolts, MS freehub	reťaz Sram SX Eagle, 12s, Powerlock
kazeta Sram XG-1275, 10-52T, 12s	drôty DT Champion, straightpull
ráfiky DT Swiss E1900 Spline 29, 30mm internal width, sleeved aluminum, tubeless ready, 28 spokes	plášte Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead
obj.c. 010.21077SR	gripy Onoff Twin, 1lock-on, 135mm
tlmič Fox Float DPX2 LV EVOL Performance, 205x62.5mm. Settings: compression 3 positions lever, low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom	predná brzda Sram G2 RS, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
zadná brzda Sram G2 RS, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads	nastavenia tlmiče Light compression, extralight rebound, air volume spacer 0.6

prevodník

32T, CNC-machined alloy, X-SYNC 2

pätka k přehazovačce

Mondraker M068
