

CRAFTY CARBON RR SL, CARBON/BLACK/SILVER, 2021

obj. č.: 638984766



Odporúčaná cena

12.999,00 EUR

Technické špecifikácie

vyrábané veľkosti

S 380mm / M 420mm / L 450mm / XL 490mm

hmotnosť

20,1 Kg

rám

Crafty Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.

vidlica

Fox 36 29 Float FIT4 EVOL Factory Kashima, 160mm, e-bike optimized, tapered steerer tube, Boost 15x110mm axle, 44mm offset, 68mm OD crown. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload

hlavové zloženie

Acros custom for 1-1/2 head tube, angular contact bearings 40x52x7, Internal cable routing

prehadzovačka

Sram X01 Eagle AXS, Type 2.1 roller bearing clutch, cage lock, long carbon cage, 1x12s, X-actuation 1:1

radenie

Sram Eagle AXS, 12s

brzdové páčky

Shimano XTR M9120, ergonomic antiskid lever with servo wave, tool less reach adjust, free stroke adjust

kluky

E.13 TRS Race carbon ebike, 165mm

riadidlá

Onoff Krypton Carbon 1.0, rise: 25mm, width: 780mm, 9 backsweep, 5 upsweep, 31.8mm barbare, Onoff Desert, 11lock-on, 135mm, sizes: S/M L/XL

predstavec


Onoff Krypton FG 30mm, 6061 forged alloy, 31.8mm barbare

sedlovka

RockShox Reverb Stealth AXS, diameter 31.6mm, S size: 390x125mm, M size: 440x150mm, L/XL size: 440x170mm

sedlo FIZIK ANTARES LARGE R1	náboj predný DT 240, Boost 15x110mm, CenterLock
náboj zadný DT 240, Boost 12x148mm, 24T Ratchet system, CenterLock	reťaz Sram GX Eagle, 12s, Powerlock
kazeta Sram XG-1295, 10-50T, 12s	drôty DT Hybrid SP, straightpull
ráfiky DT Swiss HXC1200 Carbon Spline 29, 30mm internal width, hookless, tubeless ready, 28 spokes	obj.c. 010.21267
tlmič Fox Float DPS Factory Kashima, 205x65mm. Settings: Compression 3 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings	predná brzda Shimano XTR M9120, 4 piston caliper, MT900 ICE-Tech 203mm CenterLock rotor, resin pads with fin
zadná brzda Shimano XTR M9120, 4 piston caliper, MT910 ICE-Tech 203mm CenterLock rotor, resin pads with fin	plášť zadný Maxxis Rekon 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
nastavenia tlmiče Medium compression, Medium rebound, 0.4 volume spacer	prevodník Sram X-Sync 2 Eagle 34T, alloy, narrow-wide, 104 BCD
pätko k prehadzovačke Mondraker M068	motor + batérie Bosch Performance Line CX Cruise (25Km/h) GEN4, computer Bosch Kiox, Bosch Powertube 625Wh

Geometria



GEOMETRY

Size	S	M	L	XL
A Seat Tube Length	380 mm	420 mm	450 mm	480 mm
B Top Tube Length	605 mm	625 mm	650 mm	670 mm
C Bottom Bracket Drop	-25 mm	-25 mm	-25 mm	-25 mm
D Bottom Bracket Height	350 mm	350 mm	350 mm	350 mm
E Chainstay Legth	455 mm	455 mm	455 mm	455 mm
F Seat Tube Angle, Actual	73.5°	73.5°	73.5°	73.5°
G Seat Tube Angle, Effective	76°	76°	76°	76°
H Head Tube Angle	65.5°	65.5°	65.5°	65.5°
I Fork Offset	44 mm	44 mm	44 mm	44 mm
J Wheelbase	1225 mm	1245 mm	1270 mm	1290 mm
K Head Tube Length	110 mm	110 mm	130 mm	130 mm
L Reach	450 mm	470 mm	490 mm	510 mm
M Stack	622 mm	622 mm	640 mm	640 mm