

# chybí obrázek

## Technické špecifikácie

|                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>vyrábané veľkosti</b><br>S: 390mm / M: 420mm / L: 470mm / XL: 510mm                                                                                                                                                               | <b>rám</b><br>F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 100mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount. |
| <b>vidlica</b><br>Fox 34 Step Cast Float FIT4 Evol Factory Kashima, 110mm, tapered steerer tube,15x110mm Boost axle, offset 44mm. Settings: remote 2pos Push-unlock, compression micro-adjustment at low-speed, rebound, air preload | <b>hlavové zloženie</b><br>Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom                                                                                                                                                                                                                                      |
| <b>prehadzovačka</b><br>Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1                                                                                                                              | <b>radenie</b><br>Sram Trigger GX Eagle, 12s, X-Actuation 1:1                                                                                                                                                                                                                                                              |
| <b>brzdové páčky</b><br>Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings                                                                                                                              | <b>kluky</b><br>Sram X1 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S size: 170mm, M/L/XL size: 175mm                                                                                                                                                                                                          |
| <b>stredové zloženie</b><br>Sram DUB BSA, sealed bearings, 73mm                                                                                                                                                                      | <b>riadidlá</b><br>Onoff Helium Carbon 0.2, rise: 4.8mm, width: 760mm, 9º backsweep, 0º upsweep, 31.8mm barbore                                                                                                                                                                                                            |
| <b>predstavec</b><br>MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5º, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm                                                                                                           | <b>sedlovka</b><br>Onoff Helium Carbon 0-R, diameter 31.6mm, length 400mm                                                                                                                                                                                                                                                  |
| <b>sedlo</b><br>Fizik Antares R7                                                                                                                                                                                                     | <b>náboj predný</b><br>Mavic, Boost 15x110mm, IS 6 bolts                                                                                                                                                                                                                                                                   |
| <b>náboj zadný</b><br>Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub                                                                                                                                            | <b>refaz</b><br>Sram GX Eagle, 12s, Powerlock                                                                                                                                                                                                                                                                              |
| <b>kazeta</b><br>Sram XG-1275, 10-50T, 12s                                                                                                                                                                                           | <b>drôty</b><br>Mavic straightpull duple butted, contactless lacing                                                                                                                                                                                                                                                        |
| <b>ráfiky</b><br>Mavic Crossmax Carbon XL R 29, 30mm internal width, hookless, tubeless ready, 24 spokes                                                                                                                             | <b>plášte</b><br>Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead, Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead                                                                                                                                          |
| <b>obj.c.</b><br>010.22048                                                                                                                                                                                                           | <b>gripy</b><br>Onoff Diamond, 1lock-on, 135mm                                                                                                                                                                                                                                                                             |
| <b>tlmič</b><br>Fox Float DPS SV EVOL Factory Kashima, 185x47,5mm. Settings: 2 position remote compression (open/lock), low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings                                | <b>predná brzda</b><br>Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad                                                                                                                                                                                               |
| <b>zadná brzda</b><br>Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad                                                                                                          | <b>nastavenia tlmiče</b><br>Firm compression, light rebound, air volume spacer 0.2                                                                                                                                                                                                                                         |
| <b>prevodník</b><br>34T, CNC-machined alloy, X-SYNC 2                                                                                                                                                                                | <b>pätka k preházoačce</b><br>Sram UDH                                                                                                                                                                                                                                                                                     |