

chybí obrázek

Technické špecifikácie

vyrábané veľkosti One size: 260mm	rám Play 20 6061 Alloy Stealth evo, hydroformed tubing, integrated internal non-removable battery, Tapered head tube, HHG internal cable routing, BSA bottom bracket, QR 9mm rear axle, 1x drivetrain compatible
vidlica MDK 20 Kid, Rigid alloy Stealth stanchions, Post Mount disc brake mount	hlavové zloženie Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
prehadzovačka Microshift M26S, 9s, short cage	radenie Microshift Mezzo TS39-9, 9s
brzdové páčky Sram Level, tooled reach adjust, lever pivot bushings	kluky Samox DM 28T steel, 114mm
stredové zloženie BSA, 73mm	riadičlá MDK XC 1.0, 6061 alloy, rise: 25mm, width: 580mm, 9° backsweep, 5° upsweep, 31.8mm barbore
predstavec Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore	sedlovka MDK XC 0-R, 6061 T6 Alloy, diameter 31.6mm, length 250mm
sedlo MDK Play 20	náboj predný Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts
náboj zadný Mahle-Ebikemotion X-35	reťaz Sram PC951 9s, Powerlock
kazeta Microshift Mezzo 11-34T, 9s	dróty CN round stainless steel
ráfiky MDK-XP1 20 TLR, 25mm internal width, tubeless ready, 32 spokes	plášte Kenda Booster 20x2.4 single compound 30TPI, wire bead
obj.c. 010.23207	gripy Onoff Twin, 1lock-on
predná brzda Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	zadná brzda Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
prevodník 28T, steel	pätka k preházoačce Mondraker M073
motor + batérie Mahle-Ebikemotion X-35, Mahle-Ebikemotion Internal 250Wh, Mahle-Ebikemotion	