

chybí
obrázek

Odporúčaná cena

0,00 EUR

Technické špecifikácie

vyrábané veľkosti S: 395mm / M: 430mm / L: 470mm / XL: 520mm	rám Chrono 29 Stealth full Carbon, XC Forward Geometry, 73mm BSA bottom bracket, tapered head tube, HHG Internal Cable routing, Boost 12x148mm rear axle, Comfort Flat chainstays (Flatstays) design
vidlica RockShox Judy Gold RL 29, 100mm, Motion control, Solo Air, tapered steerer tube, Boost 15x110mm axle, 30mm aluminum stanchions, offset 51mm. Settings: Onelock 2 pos remote compression (open/lock), rebound, air preload, RockShox OneLoc	hlavové zloženie Onoff Titan tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41.8x30.5x8x45°x45°, bottom 51.9x40x8x45°x45°
prehadzovačka Sram NX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1	radenie Sram Trigger SX Eagle, 12s, X-Actuation 1:1
brzdové páčky Sram Level, tooled reach adjust, lever pivot bushings	kluky Sram SX Eagle, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm
stredové zloženie Sram DUB BSA, sealed bearings, 73mm	riadidlá Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbare
predstavec MDK, 6061 T6 Alloy, 31.8mm barbare, rise: +/-5°, length: size S: 60mm, size M: 70mm, size L: 80mm, size XL: 90mm	sedlovka Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 27.2mm, length 400mm
sedlo Mondraker XC Series, steel rail	náboj predný Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts
náboj zadný Formula MST148S-4SB, Boost 12x148mm, sealed bearings, IS 6 bolts	reťaz Sram SX Eagle, 12s, Powerlock
kazeta Sram XG-1230, 11-50T, 12s	drôty CN round stainless steel
ráfiky MDK-XP1 29 TLR, 25mm internal width, tubeless ready, 32 spokes	plášte Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead
obj.c. 010.23025	gripy Onoff Twin, 1lock-on, 135mm
predná brzda Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	zadná brzda Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
prevodník 34T, steel, X-Sync 2	pätka k prehadzovačke Mondraker M068