

chybí
obrázek

Odporúčaná cena

0,00 EUR

Technické špecifikácie

vyrábané veľkosti S: 380mm / M: 420mm / L: 450mm / XL: 490mm	hmotnosť 25,1kg
rám Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.	vidlica Fox 38 29 Float FIT GRIP EVOL Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
hlavové zloženie Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°	prehadzovačka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
radenie Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click	brzdové páčky Sram G2 R, tool-free reach adjust
kľuky Race Face Aeffect ebike, 165mm	riadidlá Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
predstavec Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare	sedlovka Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm
sedlo FIZIK Terra Aidon X5 145mm	náboj predný Mavic, Boost 15x110mm, IS 6 bolts
náboj zadný Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts	retaz Sram SX Eagle, 12s, Powerlock
kazeta Sram PG-1210, 11-50T, 12s	drôty Mavic J-bend duble butted, contactless lacing
ráfiky Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes	plášte Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead, Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
obj.c. 010.22224	gripy Onoff Diamond, 1lock-on, 135mm
tlmič Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings	predná brzda Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
zadná brzda Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads	nastavenia tlmiče medium compression, medium rebound, air volume spacer 0.2

prevodník

Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

pátka k přehazovačce

Mondraker M068

motor + batérie

Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3, Bosch
Powertube 750Wh, Bosch Kiox 300