

chybí obrázek

Technické špecifikácie

vyrábané veľkosti S: 380mm / M: 420mm / L: 470mm / XL: 510mm	rám F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 115mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.
vidlica Rockshox SID Ultimate RL 29, 120mm, Charger Race day, DebonAir, tapered steerer tube, Boost 15x110mm axle, 35mm tapered aluminum stanchions, offset 44mm. Settings: OneLoc, Low-speed rebound, air preload, RockShox OneLoc	hlavové zloženie Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom
prehadzovačka Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	radenie Sram Trigger GX Eagle, 12s, X-Actuation 1:1
brzdové páčky Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings	kluky Sram X1 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S size: 170mm, M/L/XL size: 175mm
stredové zloženie Sram DUB BSA, sealed bearings, 73mm	riadiidlá Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm harbore
predstavec MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5°, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm	sedlovka Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm
sedlo Fizik Antares R7	náboj predný Infinity hub, Boost 15x110mm, IS 6 bolts
náboj zadný Infinity hub, ID360 freewheel technology, Boost 12x148mm, IS 6 bolts	reťaz Sram GX Eagle, 12s, Powerlock
kazeta Sram XG-1275, 10-50T, 12s	drôty 24 straight-pull double butted spokes
ráfiky Mavic CrossMax Carbon XL R, 29 Boost 30mm internal width, hookless, tubeless ready, 24 spokes	plášte Maxxis Rekon Race 29x2.4, EXO protection, tubeless ready, 120TPI, folding bead
obj.c. 010.23065	gripy Onoff Desert, 1lock-on, 135mm
tlmič Rockshox SID Luxe Ultimate RLR DebonAir, 185x50mm. Settings: OneLoc, low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings	predná brzda Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
zadná brzda Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad	nastavenia tlmiče Light compression, medium rebound, Lockout 430, 1 Token
prevodník 34T, CNC-machined alloy, X-SYNC 2	pätka k prehadzovačke Sram UDH