

chybí obrázek

Technické špecifikácie

vyrábané veľkosti S: 380mm / M: 420mm / L: 470mm / XL: 510mm	rám Podium 29 Stealth Air Carbon, XC Forward Geometry, BSA bottom bracket, tapered head tube, HHG internal cable routing, Boost 12x148mm rear axle, dedicated 1X drivetrain design, Flatmount brake compatible,
vidlica Rockshox SID SL Ultimate RL 29, 100mm, Charger Race day, DebonAir, tapered steerer tube, Boost 15x110mm axle, 32mm aluminum stanchions, offset 44mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload, RockShox OneLoc	hlavové zloženie Onoff Titan tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41.8x30.5x8x45°x45°, bottom 51.9x40x8x45°x45°
prehadzovačka Sram XX1 Eagle AXS, Type 2.1 roller bearing clutch, cage lock, long carbon cage, 1x12s, X-actuation 1:1, Battery protection	radenie Sram Eagle AXS Rocker paddle, 12s
brzdové páčky Sram Level Ultimate, carbon lever, Direct Link actuation, tooled reach adjust, lever pivot bearings, titanium hardware	kluky Sram XX1 Eagle, Boost, DUB axle, Direct mount chain ring, S size: 170mm, M/L/XL size: 175mm
stredové zloženie Sram DUB BSA, sealed bearings, 73mm	riadidlá Onoff Helium Carbon 0.2, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbore
predstavec Onoff Helium 7075 alloy CNC, 31.8mm barbore, rise: +/-8°, length: sizes S/M: 60mm, size L: 70mm, size XL: 80mm	sedlovka Onoff Helium Carbon 0-R VFLEX, diameter 27.2mm, length 400mm
sedlo Fizik Antares R7	náboj predný Mavic, Boost 15x110mm, IS 6 bolts
náboj zadný Mavic, Boost 12x148mm, ID360 Ratchet system, IS 6 bolts, XD freehub	reťaz Sram XX1 Eagle, 12s rainbow, Powerlock
kazeta Sram XG-1299 10-50T, 12s	drôty Mavic straight-pull double butted, contactless lacing
ráfiky Mavic Crossmax Carbon SL Ultimate 29, 25mm internal width, hookless, tubeless ready, 24 spokes	plášte Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead
obj.c. 010.23045	gripy LIZARD DSP 30.3
predná brzda Sram Level Ultimate, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad, titanium hardware	zadná brzda Sram Level Ultimate, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad, titanium hardware
prevodník 34T, CNC-machined alloy, X-SYNC 2	pätka k prehadzovačke Sram UDH