

chybí obrázek

Technické špecifikácie

vyrábané veľkosti S: 390mm / M: 420mm / L: 470mm / XL: 510mm	rám F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 115mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.
vidlica Rockshox SID Ultimate RL 29, 120mm, Charger Race day, Debonair, tapered steerer tube, Boost 15x110mm axle, 35mm tapered aluminum stanchions, offset 44mm. Settings: TwistLock 2 position remote compression (open/lock), low-speed rebound, air preload	hlavové zloženie Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom
prehadzovačka Sram XX1 Eagle AXS, Type 2.1 roller bearing clutch, cage lock, long carbon cage, 1x12s, X-actuation 1:1	radenie Sram Eagle AXS, 12s
brzdové páčky Sram Level TLM, Direct Link actuation, tooled reach adjust, lever pivot bushings	kluky Sram XX1 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S size: 170mm, M/L/XL size: 175mm
stredové zloženie Sram DUB BSA, sealed bearings, 73mm	riadiidlá Onoff Helium Carbon 0.2, rise: 4.8mm, width: 760mm, 9º backsweep, 0º upsweep, 31.8mm barbore
predstavec Onoff Helium 7075 alloy CNC, 31.8mm barbore, rise: +/-8º, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm	sedlovka RockShox Reverb Stealth AXS, diameter 31.6mm S size: 340x100mm, M size 390x125mm, L/XL size: 440x150mm
sedlo Fizik Antares R7	náboj predný Mavic, Boost 15x110mm, IS 6 bolts
náboj zadný Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub	reťaz Sram XX1 Eagle, 12s, Powerlock
kazeta Sram XG-1299, 10-50T, 12s	drôty Mavic straightpull duple butted, contactless lacing
ráfiky Mavic Crossmax Carbon XL R 29, 30mm internal width, hookless, tubeless ready, 24 spokes	plášte Maxxis Rekon Race 29x2.4, EXO protection, tubeless ready, 120TPI, folding bead, Maxxis Rekon Race 29x2.4, EXO protection, tubeless ready, 120TPI, folding bead
obj.c. 010.22060	gripy Rock Shox Twistloc grips
tlmič Rockshox SID Luxe Ultimate RLR Debonair, 185x50mm. Settings: TwistLock 2 position remote compression (open/lock), low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings	predná brzda Sram Level TLM, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
zadná brzda Sram Level TLM, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	nastavenia tlmiče Light compression, medium rebound, Lockout 430, 1 Token

prevodník
34T, CNC-machined alloy

pátka k přehazovačce
Sram UDH
