

chybí obrázek

Technické špecifikácie

vyrábané veľkosti One size: 300mm	rám F-Play 24 6061 Alloy Stealth evo, hydroformed tubing, Zero Suspension System, 120mm travel, one piece bolt-on upper link, integrated internal non-removable battery, Tapered head tube, HHG internal cable routing, BSA bottom bracket, QR 9mm rear axle, 1x drivetrain compatible
vidlica X-Fusion Velvet RL 26, 100mm, air spring, tapered steerer tube, 9x100mm axle, 32mm aluminum stanchions, 41mm offset. Settings: lockout, rebound, air preload	hlavové zloženie Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
prehadzovačka Sram GX, 10s, short cage, X-actuation 1:1	radenie Sram trigger GX 10s, X-actuation 1:1
brzdové páčky Sram Level, tooled reach adjust, lever pivot bushings	kluky Samox DM 30T steel, 152mm
stredové zloženie BSA, 73mm	riadidlá MDK XC 1.0, 6061 alloy, rise: 25mm, width: 680mm, 9° backsweep, 5° upsweep, 31.8mm barbore
predstavec Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore	sedlovka MDK XC 0-R, 6061 T6 Alloy, diameter 31.6mm, length 300mm
sedlo SDG Fly JR	náboj predný Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts
náboj zadný Mahle-Ebikemotion X-35	reťaz Sram PC1031 10s, Powerlock
kazeta Sram PG 1020 11-36T, 10s	drôty CN round stainless steel
ráfiky MDK-XP1 24 TLR, 25mm internal width, tubeless ready, 32 spokes	plášte Kenda Booster 24x2.4 single compound 30TPI, wire bead
obj.c. 010.23210	gripy Onoff Twin, 1lock-on
tlmič X-Fusion 02PRO R, 210x47.5mm. Settings: low-speed rebound, air preload. 45x8mm top and bottom bushings	predná brzda Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
zadná brzda Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	nastavenia tlmiče A-Tune light compression
prevodník 30T, steel	pätka k prehadzovačke Mondraker M073
motor + batérie Mahle-Ebikemotion X-35, Mahle-Ebikemotion Internal 250Wh, Mahle-Ebikemotion	