

chybí  
obrázek

Odporúčaná cena  
**0,00 EUR**

Technické špecifikácie

|                                                                                                                                                                                                       |                                                                                                                                                              |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>vyrábané veľkosti</b><br>S: 395mm / M: 430mm / L: 470mm / XL: 520mm                                                                                                                                | <b>rám</b><br>Chrono 29 Stealth Alloy, XC Forward Geometry, 73mm BSA bottom bracket, tapered head tube, HHG Internal Cable Routing, Boost 12x148mm rear axle |
| <b>vidlica</b><br>Fox 32 29 Float GRIP EVOL Rhythm, 120mm, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: remote 2pos Push-unlock, low-speed rebound, air preload, Fox single pull | <b>hlavové zloženie</b><br>Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°         |
| <b>prehadzovačka</b><br>Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1                                                                                                | <b>radenie</b><br>Sram Trigger SX Eagle, 12s, X-Actuation 1:1                                                                                                |
| <b>brzdové páčky</b><br>Sram Level, tooled reach adjust, lever pivot bushings                                                                                                                         | <b>kľuky</b><br>Truvativ Stylo 6K Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm                                    |
| <b>stredové zloženie</b><br>Sram DUB BSA, sealed bearings, 73mm                                                                                                                                       | <b>riadidlá</b><br>Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 740mm, 9° backsweep, 0° upsweep, 31.8mm barbore                           |
| <b>predstavec</b><br>Onoff Sulfur, 6061 T6 Alloy, 31.8mm barbore, rise: +/-7°, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm                                                                   | <b>sedlovka</b><br>Onoff Pija dropper internal, diameter 31.6mm, S/M size: 405x95-125mm, L/XL size 458x120-150mm                                             |
| <b>sedlo</b><br>Mondraker XC Series, steel rail                                                                                                                                                       | <b>náboj predný</b><br>Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts                                                                            |
| <b>náboj zadný</b><br>Formula MST148S-4SB, Boost 12x148mm, sealed bearings, IS 6 bolts                                                                                                                | <b>reťaz</b><br>Sram SX Eagle, 12s, Powerlock                                                                                                                |
| <b>kazeta</b><br>Sram PG-1210, 11-50T, 12s                                                                                                                                                            | <b>drôty</b><br>CN round stainless steel                                                                                                                     |
| <b>ráfiky</b><br>MDK-XP1 29 TLR, 25mm internal width, tubeless ready, 32 spokes                                                                                                                       | <b>plášte</b><br>Maxxis Ardent 29x2.40, 60TPI, folding bead                                                                                                  |
| <b>obj.c.</b><br>010.23021                                                                                                                                                                            | <b>gripy</b><br>Onoff Twin, 1lock-on, 135mm                                                                                                                  |
| <b>predná brzda</b><br>Sram Level, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad                                                                             | <b>zadná brzda</b><br>Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad                                     |
| <b>prevodník</b><br>34T, steel, X-Sync 2                                                                                                                                                              | <b>pätka k prehadzovačke</b><br>Mondraker M068                                                                                                               |