

chybí

obrázek

Technické špecifikácie

vyrábané veľkosti S: 395mm / M: 430mm / L: 470mm / XL: 520mm	rám Chrono 29 Stealth full Carbon, XC Forward Geometry, 73mm BSA bottom bracket, tapered head tube, HHG Internal Cable routing, Boost 12x148mm rear axle, Comfort Flat chainstays (Flatstays) design
vidlica Fox 32 29 Float GRIP EVOL Rhythm, 100mm, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: remote 2pos Push-unlock, low-speed rebound, air preload, Fox single pull	hlavové zloženie Onoff Titan tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41.8x30.5x8x45°x45°, bottom 51.9x40x8x45°x45°
prehadzovačka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	radenie Sram Trigger NX Eagle, 12s, X-Actuation 1:1
brzdové páčky Sram Level, tooled reach adjust, lever pivot bushings	kľuky Truvativ Stylo 6K Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm
stredové zloženie Sram DUB BSA, sealed bearings, 73mm	riadidlá Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbore
predstavec MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5°, length: size S: 60mm, size M: 70mm, size L: 80mm, size XL: 90mm	sedlovka Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 27.2mm, length 400mm
sedlo Mondraker XC Series, steel rail	náboj predný Mavic, Boost 15x110mm, IS 6 bolts
náboj zadný Mavic, Boost 12x148mm, ID360 Ratchet system, IS 6 bolts	reťaz Sram SX Eagle, 12s, Powerlock
kazeta Sram XG-1230, 11-50T, 12s	drôty Mavic straight-pull double butted, contactless lacing
ráfiky Mavic Crossmax 29, 25mm internal width, welded rim, hookless, tubeless ready, 24 spokes	plášte Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead
obj.c. 010.23029	gripy Onoff Twin, 1lock-on, 135mm
predná brzda Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	zadná brzda Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
prevodník 34T, steel, X-Sync 2	pätka k prehazovačke Mondraker M068